



PART NUMBER: FN-0616

KEY FEATURES:

- 180° or 40° light spread optic available
- Single color: 16 flash patterns
- Dual color: 48 flash patterns
- + Directional Patterns
- Available Colors: R, B, A, W, G, RW, BW, AW, AR, AB, RB
- Bracket options: Rotating, Headliner, Single L-Bracket, Double L-Bracket, End-Cap Mount
- Encased in rugged, aluminum extrusion

QUICK FACTS:

- Made in the USA
- Certifications: SAE J595, CT13, SAE J1113-11
- Available in single color or dual color
- Capabilities:
 - 1 programmable mode for single color
 - 2 programmable modes for dual color
 - Takedown or Work-light
 - Flood mode for dual color

SPECIFICATIONS:

Dimensions	1.22" H x 28.14" L x 2.25" W
Warranty	5 years
Cable Harness Length	10 feet

Voltage	12VDC
Current Draw	4A (fuse @125%)
Single Color	36 high power 4 Watt Cree LED's
Dual Color	72 high power 4 Watt Cree LED's

WIRING CHART:

Wire Color:	Single Color:	Dual Color:
Black	12V (-)	12V (-)
Red	12V (+)	12V (+)
White	Takedown* 12V+	Takedown*/Flood
Yellow	Pattern Change 12V (+)	Pattern Change
Green	Takedown Flashing* 12V+	Mode Two
Blue	Left Arrow 12V+	Left Arrow
Brown	Mode One 12V+	Mode One
Gray	Right Arrow 12V+	Right Arrow