



# Q<sup>®</sup> SERIES

Serial Technology with 31 Available Color Settings: Single, Dual, Tri, Quad, & Quint.

Feniex Industries, Inc.  
1.800.615.8350

## Q-FLAT-WIDE SURFACE MOUNT

Perimeter



<b>PART #</b>	QFWS-8101
<b>DIMENSIONS</b>	9.625" x 0.56" x 1"
<b>VOLTAGE</b>	10-18VDC
<b>CURRENT DRAW</b>	2 Amps @ 13V
<b>INPUTS</b>	27 Inputs
<b>FLASH PATTERNS</b>	Over 20
<b>OPTICS</b>	60° Wide Spread
<b>LED COLORS</b>	
<b>LED COUNT</b>	54 LEDs
<b>CABLE LENGTH</b>	1ft

### CERTIFICATIONS:



### DESCRIPTION:

Introducing the Feniex Q-Flat-Wide Surface Mount (Serial), the first 5-color, serial perimeter light with two low-profile lightheades stacked horizontally for twice the brightness. Engineered for a stream-lined, sleek exterior, this cutting-edge surface mount light offers a spectrum of colors including Blue, Red, Amber, White, and Green, empowering you to command attention and enhance safety in any situation. The Feniex Q<sup>®</sup> Series lightheades are built with state-of-the-art serial technology that connects using 2 serial wires to the Q<sup>®</sup> Link device.

- Blue, Red, Amber, White, and Green colors in each module
- Syncs with up to 48 lightheades using one Q Link
- Computer programmable with Q Link Software
- 27 programmable inputs with the Q Link (sold separately)
- Available functions include Flood, Cruise, and Stop Tail Turn and more



Military-grade aluminum



Anti-yellowing & anti-cracking clear-coated polycarbonate lens